



## HJ H Series



### Application

- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in outdoor applications for full weather protection.

### Standards

- UL 508A Type 3R, 4, 12 and 13
- CSA Type 3R, 4, 12 and 13
- Complies with
  - NEMA Type 3R, 4, 12 and 13
  - IEC 60529, IP66

### Construction

- Body formed from 16 gauge or 14 gauge steel. Covers are formed from 14 gauge steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Welded brackets provide for enclosure mounting.
- Continuous hinged cover is secured with stainless steel clamps and screws.
- Stainless steel continuous hinge on door may be removed by pulling the stainless steel hinge pin.
- Seamless poured-in place gasket.
- Internal threaded weld studs are provided for mounting inner panels.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure

### Finish

- Cover and enclosure are phosphatized, finished in recoatable smooth ANSI 61 gray powder coating.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*

## Type 4, 12 Mild Steel Junction Box *HJ H Series*

Continuous Hinge Door with Clamps

ANSI 61 Gray Part No.	Enclosure			Optional Inner Panel		
	H	3.50	3.25	Part Number	H	W
<a href="#">HJ443HLP</a>	4.00	4.00	3.00	No Panel		
<a href="#">HJ643HLP</a>	6.00	4.00	3.00	<a href="#">14R0503</a>	4.88	2.88
<a href="#">HJ863HLP</a>	8.00	6.00	3.50	<a href="#">14R0705</a>	6.75	4.88
<a href="#">HJ683HLP</a>	6.00	8.00	3.50	<a href="#">14R0705</a>	6.75	4.88
<a href="#">HJ444HLP</a>	4.00	4.00	4.00	No Panel		
<a href="#">HJ644HLP</a>	6.00	4.00	4.00	<a href="#">14R0503</a>	4.88	2.88
<a href="#">HJ664HLP</a>	6.00	6.00	4.00	<a href="#">14R0505</a>	4.88	4.88
<a href="#">HJ884HLP</a>	8.00	8.00	4.00	<a href="#">14R0707</a>	6.75	6.88
<a href="#">HJ1084HLP</a>	10.00	8.00	4.00	<a href="#">14R0907</a>	8.75	6.88
<a href="#">HJ8104HLP</a>	8.00	10.00	4.00	<a href="#">14R0907</a>	8.75	6.88
<a href="#">HJ1264HLP</a>	12.00	6.00	4.00	<a href="#">14R1105</a>	10.75	4.88
<a href="#">HJ12105HLP</a>	12.00	10.00	5.00	<a href="#">14R1109</a>	10.75	8.88
<a href="#">HJ10125HLP</a>	10.00	12.00	5.00	<a href="#">14R1109</a>	10.75	8.88
<a href="#">HJ866HLP</a>	8.00	6.00	6.00	<a href="#">14R0705</a>	6.75	4.88
<a href="#">HJ1086HLP</a>	10.00	8.00	6.00	<a href="#">14R0907</a>	8.75	6.88
<a href="#">HJ10106HLP</a>	10.00	10.00	6.00	<a href="#">14R0909</a>	8.75	8.88
<a href="#">HJ12126HLP</a>	12.00	12.00	6.00	<a href="#">14R1111</a>	10.75	10.88
<a href="#">HJ1486HLP</a>	14.00	8.00	6.00	<a href="#">14R1307</a>	12.75	6.88
<a href="#">HJ14126HLP</a>	14.00	12.00	6.00	<a href="#">14R1311</a>	12.75	10.88
<a href="#">HJ12146HLP</a>	12.00	14.00	6.00	<a href="#">14R1311</a>	12.75	10.88
<a href="#">HJ16106HLP</a>	16.00	10.00	6.00	<a href="#">14R1509</a>	14.75	8.88
<a href="#">HJ16146HLP</a>	16.00	14.00	6.00	<a href="#">14R1513</a>	14.75	12.88
<a href="#">HJ14166HLP</a>	14.00	16.00	6.00	<a href="#">14R1513</a>	14.75	12.88
<a href="#">HJ12108HLP</a>	12.00	10.00	8.00	<a href="#">14R1109</a>	10.75	8.88
<a href="#">HJ14128HLP</a>	14.00	12.00	8.00	<a href="#">14R1311</a>	12.75	10.88
<a href="#">HJ16148HLP</a>	16.00	14.00	8.00	<a href="#">14R1513</a>	14.75	12.88
<a href="#">HJ161410HLP</a>	16.00	14.00	10.00	<a href="#">14R1513</a>	14.75	12.88