



## HN4 FS Series



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls with provision for panel mounting or rack mounting of equipment.
- Provides protection where equipment may be hosed down or otherwise be very wet or in specific applications where corrosion is a critical problem.
- Various inner panels, rack mounting rails and swing-out frames are available to provide flexibility in mounting arrangements.

### Standards

- UL 508A Type 3R, 4 and 12
- CSA Type 3R, 4 and 12
- Complies with
  - NEMA Type 3R, 4, 12 and 13
  - IEC 60529, IP66

### Construction

- Formed 12 gauge steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Lifting eyes provide for easy enclosure handling.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in-place gasket.
- Provision for light kit mounting.
- A grounding stud is provided in the enclosure, and a bonding stud is provided on the door. Mounting channels are welded inside the enclosure for mounting optional inner panels or rack equipment rails.

### Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.
- Optional inner panels are available in white powder coating or unpainted galvanized steel.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*


---

**Type 4 Mild Steel Freestanding Enclosure** *HN4 FS Series*

 Continuous Hinge Door with Handle
 

---

Part No.	Enclosure			Optional
	H	W	D	Panel
<a href="#">HN4FS722518</a>	72.06	25.06	18.06	<a href="#">72WFW</a>
<a href="#">HN4FS723124</a>	72.06	31.06	24.06	<a href="#">72XFW</a>
<a href="#">HN4FS723724</a>	72.06	37.06	24.06	<a href="#">72YFW</a>