



# Automation & Power Incorporated

## HN4 WM Series



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments
- Provides protection where equipment may be hosed down or otherwise be very wet, or in outdoor applications for full weather protection.

### Standards

- UL 508A Type 3R, 4, and 12
- CSA Type 3R, 4, and 12
- Complies with
  - NEMA Type 3R, 4, 12 and 13
  - IEC 60529, IP66

### Construction

- Formed 12 gauge steel
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Doors are supported with heavy gauge continuous hinges.
- 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.

### Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.
- Removable inner panel is finished in white powder coating.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*

## Type 4 Two Door Wallmount Enclosure *HN4 WM Series*

Continuous Hinge Door with Handle

Part No.	Enclosure			Inner Panel	
	H	W	D	H	W
<a href="#">HN4WM24428GY</a>	24.00	42.00	8.00	21.00	39.00
<a href="#">HN4WM24488GY</a>	24.00	48.00	8.00	21.00	45.00
<a href="#">HN4WM304210GY</a>	30.00	42.00	10.00	27.00	39.00
<a href="#">HN4WM304810GY</a>	30.00	48.00	10.00	27.00	45.00
<a href="#">HN4WM306010GY</a>	30.00	60.00	10.00	27.00	57.00
<a href="#">HN4WM364212GY</a>	36.00	42.00	12.00	33.00	39.00
<a href="#">HN4WM364812GY</a>	36.00	48.00	12.00	33.00	45.00
<a href="#">HN4WM366012GY</a>	36.00	60.00	12.00	33.00	57.00
<a href="#">HN4WM424212GY</a>	42.00	42.00	12.00	39.00	39.00
<a href="#">HN4WM424812GY</a>	42.00	48.00	12.00	39.00	45.00
<a href="#">HN4WM426012GY</a>	42.00	60.00	12.00	38.00	56.00
<a href="#">HN4WM484812GY</a>	48.00	48.00	12.00	44.00	44.00