




## Eclipse Series



### Application

- Designed to house the following safety disconnect equipment:
  - ABB Controls flange mounted variable depth operating mechanisms for disconnect switches and circuit breakers. Cable version for circuit breakers also available.
  - Allen Bradley 1494V and 1494U variable depth flange mounted disconnect switches and circuit breaker mechanisms.
  - Cutler Hammer C361 variable depth flange mounted disconnect switches and C371 circuit breaker operators. Also Flex-Shaft™ handle mechanisms for circuit breakers. Use Cutler Hammer NEMA 4X rated operating handles to maintain NEMA 4X integrity.
  - Siemens I-T-E Max-Flex™ flange mounted variable depth handles for disconnect switch and circuit breakers. Use handle for NEMA 4 rating.
  - General Electric Type STDA flange handles and variable depth operating mechanisms for disconnect switches and circuit breakers. Also SpectraFlex™ cable operators for circuit breakers.
  - Square D Class 9422 disconnect switches with flange mounted variable depth operating mechanisms or cable mechanisms and Class 9422 flange mounted variable depth operating mechanism or cable mechanisms for circuit breakers. SN4SS enclosures will not accept Square D Class 9422 bracket-mounted disconnect devices, 9422TG1 or TG2 devices.
- Refer to the Type 4 Wallmount Selection Guide.

### Standards

- UL 508A Type 3R, 4 and 4X
- CSA Type 3R, 4 and 4X
- Complies with
  - NEMA Type 3R, 4, 12 and 13
  - IEC 60529, IP66
- Appropriate components are required to maintain these standards.



## Automation & Power Incorporated

### Construction

- Formed 14 gauge doors with 16 or 14 (36x32" and larger) gauge type 304 stainless steel
- Continuously welded seams.
- Larger sizes include door stiffeners.
- Formed lip on door and enclosure exclude flowing liquids and contaminants.
- Cutouts and holes are provided to suit the flange handle operating mechanism.
- Doors may be easily removed for modifications and are interchangeable.
- Door is secured with easily operated 2 or 3 point, padlockable handle.
- Cover interlock bracket is included on the door.
- Collar studs are provided for mounting inner panels.
- Removable inner panel is sold separately.
- Seamless poured-in place gasket.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure
- Includes hardware kit with panel mounting nuts and sealing washers for wall mounting holes.

### Finish

- Disconnects and operating mechanisms are not provided with the enclosure, and must be ordered separately from the manufacturer.



Quality Products. Service Excellence.

## Type 4X Stainless Steel Wallmount Disconnect Enclosure *Eclipse Series*

Hinge Door with Handle (Flange w/ multi-vendor cutout)

Part No.	Enclosure			Optional Inner Panel		
	H	W	D	Part No.	H	W
<a href="#">EN4DSC20228SS</a>	20.00	22.00	8.00	<a href="#">EP2020</a>	18.17	18.17
<a href="#">EN4DSC24228SS</a>	24.00	22.00	8.00	<a href="#">EP2420</a>	22.17	18.17
<a href="#">EN4DSC24268SS</a>	24.00	26.00	8.00	<a href="#">EP2424</a>	22.17	22.17
<a href="#">EN4DSC30268SS</a>	30.00	26.00	8.00	<a href="#">EP3024</a>	28.17	22.17
<a href="#">EN4DSC36268SS</a>	36.00	26.00	8.00	<a href="#">EP3624</a>	34.17	22.17
<a href="#">EN4DSC36328SS</a>	36.00	32.00	8.00	<a href="#">EP3630</a>	34.17	28.17
<a href="#">EN4DSC423212SS</a>	42.00	32.00	12.00	<a href="#">EP4230</a>	40.17	28.17
<a href="#">EN4DSC423812SS</a>	42.00	38.00	12.00	<a href="#">EP4236</a>	40.17	34.17
<a href="#">EN4DSC483812SS</a>	48.00	38.00	12.00	<a href="#">EP4836</a>	46.17	34.17
<a href="#">EN4DSC603812SS</a>	60.00	38.00	12.00	<a href="#">EP6036</a>	58.17	34.17