

Automation & Power Incorporated

PHW Series





Application

- These enclosures are specially designed to accommodate electrical, electronic, instrumentation and mechanical controls indoors and outdoors.
- For use where corrosion resistant watertight enclosures are needed to provide protection against windblown dust and rain, splashing and hose directed water.

Standards

- UL 508A 1, 3, 3R, 4, 4X, 12
- CSA 1, 3, 3R, 4, 4X, 12
- Complies with
 - NEMA 1, 3, 3R, 4, 4X, 12
 - IEC 60529, IP 66

Construction



- Memory retaining, continuous door gasket standard.
- Molded in panel mounting inserts (except where noted).
- Integral mounting feet.
- Stainless steel hardware.
- Padlocking provision.
- Stainless steel butterfly type "twist latch" door fasteners.
- Ported with a continuous hinge.
- For corrosion resistance information, please refer to table in the Technical Information section.









Finish

Fiberglass reinforced material is finished in light gray.



Automation & Power Incorporated



Quality Products. Service Excellence.

Type 4X Polyester Wallmount Enclosure PHW Series

Continuous Hinge Door with Twist Latches

	Enclosure			Optional Inner Panel		
Part No.	Н	W	D	Н	W	Part No.
PHW20166	22.75	16.87	7.77	17.00	13.00	18P1713
PHW30247	33.41	26.32	8.81	27.00	21.00	<u>18P2721</u>
PHW20168	22.75	16.87	9.77	17.00	13.00	<u>18P1713</u>
PHW24208	27.00	21.24	9.90	21.00	17.00	<u>18P2117</u>
PHW30208	32.86	20.99	9.89	27.00	17.00	<u>18P2717</u>
PHW201610	22.75	16.87	11.77	17.00	13.00	<u>18P1713</u>
PHW241210	26.95	13.72	11.99	21.00	9.00	<u>18P2109</u>
PHW242410	27.00	25.25	11.90	21.00	21.00	<u>18P2121</u>
PHW302010	32.86	20.99	11.89	27.00	17.00	18P2717
PHW302410	33.41	26.32	11.95	27.00	21.00	<u>18P2721</u>
PHW363010	39.31	32.50	12.05	33.00	27.00	18P3327
PHW201612	22.75	16.87	13.77	17.00	13.00	<u>18P1713</u>
PHW302412	33.41	26.32	13.79	27.00	21.00	<u>18P2721</u>
PHW363012	39.31	32.50	14.05	33.00	27.00	18P3327
PHW483616	51.29	36.62	17.93	45.00	33.00	18P4533
PHW603616	63.50	36.50	18.12	57.00	33.00	18P5733