



## HN4 FM SS Series



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

### Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.
- 12" floor stands are welded to the enclosure.

### Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 13
  - IEC 60529, IP66

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable 10 gauge inner panel is finished in white powder coating.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*
**Type 4X Stainless Steel Two Door Floormount Enclosure *HN4 FM SS***
*Series*

Continuous Hinge Door with Handle

304 S.S.	316 S.S.	Enclosure			Panel	
Part No.	Part No.	H	W	D	H	W
<a href="#">HN4FM604812SS</a>	<a href="#">HN4FM604812S16</a>	60.13	48.06	12.7	56.00	44.00
<a href="#">HN4FM604818SS</a>	<a href="#">HN4FM604818S16</a>	60.13	48.06	18.7	56.00	44.00
<a href="#">HN4FM606012SS</a>	<a href="#">HN4FM606012S16</a>	60.13	60.06	12.7	56.00	56.00
<a href="#">HN4FM606018SS</a>	<a href="#">HN4FM606018S16</a>	60.13	60.06	18.7	56.00	56.00
<a href="#">HN4FM726012SS</a>	<a href="#">HN4FM726012S16</a>	72.13	60.06	12.7	68.00	56.00
<a href="#">HN4FM726018SS</a>	<a href="#">HN4FM726018S16</a>	72.13	60.06	18.7	68.00	56.00
<a href="#">HN4FM727212SS</a>	<a href="#">HN4FM727212S16</a>	72.13	72.06	12.7	68.00	68.00
<a href="#">HN4FM727218SS</a>	<a href="#">HN4FM727218S16</a>	72.13	72.06	18.7	68.00	68.00
<a href="#">HN4FM727224SS</a>	<a href="#">HN4FM727224S16</a>	72.13	72.06	24.7	68.00	68.00