



1435SS Series



Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and large amounts of water from any angle, or where highly corrosive conditions exist.

Standards

- UL 508A Type 4 and 4X
- CSA Type 4 and 4X
- Complies with
 - NEMA Type 3R, 4 and 4X
 - IEC 60529, IP66
- Appropriate components are required to maintain these standards.

Construction

- Formed 14 gauge stainless steel except sizes 1435*A and 1435*B which are 16 gauge.
- 304 or 316 SS.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Captive stainless steel cover screws thread into sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cove open during wiring.
- Oil resistant gasket.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.

Finish

- Natural stainless steel with a smooth brushed finish.


Automation & Power Incorporated

Quality Products. Service Excellence.

Type 4, 4X Stainless Steel Pushbutton Enclosures *1435SS Series*

304 S.S. 22.5mm PB Part No.	304 S.S. 30.5mm PB Part No.	316 S.S. 22.5mm PB Part No.	316 S.S. 30.5mm PB Part No.	No. Of Holes	Enclosure		
					H	W	D
<u>1435MSSA</u>	<u>1435SSA</u>	<u>1435MS16A</u>	<u>1435S16A</u>	1	3.50	3.25	2.75
<u>1435MSSB</u>	<u>1435SSB</u>	<u>1435MS16B</u>	<u>1435S16B</u>	2	5.75	3.25	2.75
<u>1435MSSC</u>	<u>1435SSC</u>	<u>1435MS16C</u>	<u>1435S16C</u>	3	8.00	3.25	2.75
<u>1435MSSD</u>	<u>1435SSD</u>	<u>1435MS16D</u>	<u>1435S16D</u>	4	10.25	3.25	2.75
<u>1435MSSH</u>	<u>1435SSH</u>	<u>1435MS16H</u>	<u>1435S16H</u>	6	9.50	6.25	3.00
<u>1435MSSK</u>	<u>1435SSK</u>	<u>1435MS16K</u>	<u>1435S16K</u>	9	9.50	8.50	3.00
<u>1435MSSO</u>	<u>1435SSO</u>	<u>1435MS16O</u>	<u>1435S16O</u>	12	11.75	8.50	3.00