

## Automation & Power Incorporated

### **PJR Series**











### **Application**



- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

#### **Standards**

- UL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- cUL Type 1, 2, 3, 4, 4X, 12 and 13 per CSA 22.2 No. 94
- Complies with
  - NEMA Type 1, 2, 3, 4, 4X, 12 and 13
  - IEC 60529, IP66

#### Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Enhanced UV inhibitors protect against outdoor weathering.
- Standard JIC sizes under 18" x 16".
- Threaded brass inserts are provided for optional inner panel or terminal kit mounting. Mounting hardware is included.
- Cover fastened with captive stainless steel screws in threaded brass inserts.
- Door fasteners include a provision for padlocking.
- Enclosures are available with bonded polycarbonate viewing windows.
- Door is supported with a continuous stainless steel hinge.
- Captive oil resistant gasket provides a positive seal.
- Threaded brass inserts are provided for mounting feet to the rear of the enclosure.
- Stainless steel mounting brackets and hardware are provided for mounting to the rear of the enclosure.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
  Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in the Technical Information section.

#### **Finish**

- Fiberglass polyester material has a gray finish.
- Optional inner panels are available in white powder coated finished steel or unfinished aluminum, or Fiberglass.



## **Automation & Power Incorporated**



Quality Products. Service Excellence.

# Type 4X Polyester Junction Box w/ Raised Lid (Solid and Window) PJ

**Series** 

Lift-Off Cover/Hinged Door with Screws

Raised Lift-Off	Raised Window	Raised Hinged	Raised Window						
Solid Cover	Cover Lift-Off	Solid Cover	Hinged Cover	Enclosure			Optional Inner Panel		
Part No.	Part No.	Part No.	Part No.	Н	W	D	Н	W	Part No.
<u>PJ664R</u>	PJ664RW	<u>PJ664RH</u>	PJ664RHW	6.10	6.10	4.18	4.88	4.88	14R0505
<u>PJ864R</u>	PJ864RW	PJ864RH	PJ864RHW	8.00	6.12	4.13	6.75	4.88	14R0705
<u>PJ1084R</u>	<u>PJ1084RW</u>	<u>PJ1084RH</u>	PJ1084RHW	10.13	8.26	4.13	8.75	6.88	14R0907
<u>PJ1086R</u>	<u>PJ1086RW</u>	<u>PJ1086RH</u>	<u>PJ1086RHW</u>	10.13	8.26	6.13	8.75	6.88	14R0907
<u>PJ12106R</u>	<u>PJ12106RW</u>	PJ12106RH	<u>PJ12106RHW</u>	12.13	10.26	6.13	10.75	8.88	14R1109
<u>PJ12124R</u>	<u>PJ12124RW</u>	<u>PJ12124RH</u>	<u>PJ12124RHW</u>	12.13	12.13	4.13	10.75	10.88	<u>14R1111</u>
PJ12126R	<u>PJ12126RW</u>	<u>PJ12126RH</u>	<u>PJ12126RHW</u>	12.13	12.13	6.13	10.75	10.88	<u>14R1111</u>
PJ14126R	<u>PJ14126RW</u>	<u>PJ14126RH</u>	<u>PJ14126RHW</u>	14.13	12.26	6.13	12.75	10.88	14R1311
<u>PJ16148R</u>	<u>PJ16148RW</u>	<u>PJ16148RH</u>	<u>PJ16148RHW</u>	16.27	14.40	8.13	14.75	12.88	14R1513
PJ18168R	<u>PJ18168RW</u>	<u>PJ18168RH</u>	<u>PJ18168RHW</u>	18.40	16.40	8.13	16.88	14.88	P1868
<u>PJ20168R</u>	<u>PJ20168RW</u>	<u>PJ20168RH</u>	<u>PJ20168RHW</u>	20.00	16.00	8.13	18.44	14.44	P2068