



## C4XSC Series



### Application

- Designed for use as a wiring box, junction box, terminal or pull box in indoor or outdoor applications where subject to hose down/precipitation or corrosion.

### Standards

- UL 508A Listed; Type 3, 4X, 12
- cULus Listed per CSA C22.2 No 94; Type 3, 4X, 12
- Complies with
  - NEMA Type 3, 4X and 12
  - IEC 60529, IP66

### Construction

- 14 gauge 304 stainless steel body up to 24"x24"; 12 gauge body when 30"x30" or larger
- 14 gauge 304 stainless steel cover up to 24"x24"; 12 gauge cover when 30"x30" or larger
- Smooth, continuously welded seams without knockouts, cutouts, or holes
- Captivated stainless steel cover screws thread into sealed wells
- Seamless poured-in place gasket
- No provision for inner mounting panel
- Mounting Foot Kit sold separately - use [C4XMTGFOOT](#)
- Replacement lid cover screws (package of 25) - use [1421A4XLCSS25SS](#)
- Replacement lid cover washers/sealed wells (package of 25) - use [1421A4XLCW25](#)

### Finish

- Enclosure and cover are unpainted, with a grained #4 finish.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*

## Type 4X Stainless Steel Junction Box C4XSC Series

Heavy Duty Screw Cover

Part No.	Enclosure		
	H	W	D
<a href="#">C4XSC664SS</a>	6.00	6.00	4.00
<a href="#">C4XSC666SS</a>	6.00	6.00	6.00
<a href="#">C4XSC864SS</a>	8.00	6.00	4.00
<a href="#">C4XSC884SS</a>	8.00	8.00	4.00
<a href="#">C4XSC886SS</a>	8.00	8.00	6.00
<a href="#">C4XSC1084SS</a>	10.00	8.00	4.00
<a href="#">C4XSC10104SS</a>	10.00	10.00	4.00
<a href="#">C4XSC10106SS</a>	10.00	10.00	6.00
<a href="#">C4XSC12124SS</a>	12.00	12.00	4.00
<a href="#">C4XSC12126SS</a>	12.00	12.00	6.00
<a href="#">C4XSC12128SS</a>	12.00	12.00	8.00
<a href="#">C4XSC16166SS</a>	16.00	16.00	6.00
<a href="#">C4XSC16168SS</a>	16.00	16.00	8.00
<a href="#">C4XSC18186SS</a>	18.00	18.00	6.00
<a href="#">C4XSC24246SS</a>	24.00	24.00	6.00
<a href="#">C4XSC24248SS</a>	24.00	24.00	8.00
<a href="#">C4XSC242410SS</a>	24.00	24.00	10.00
<a href="#">C4XSC242412SS</a>	24.00	24.00	12.00
<a href="#">C4XSC303012SS</a>	30.00	30.00	12.00
<a href="#">C4XSC363612SS</a>	36.00	36.00	12.00