



## 1414N4PHSS Series



### Application

- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion may be a problem.

### Standards

- UL 508A Type 3R, 4, 4X, 12 and 13
- CSA Type 3R, 4, 4X, 12 and 13
- Complies with
  - NEMA Type 3R, 4, 4X, 12 and 13
  - IEC 60529, IP66

### Construction

- Formed from 14 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Continuous stainless steel hinged cover is secured with stainless steel clamps and screws.
- Seamless poured-in place gasket.
- All models include a removable 14 gauge inner panel.
- Tapped studs are provided for mounting inner panels.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable inner panel is finished in white powder coating.


**Automation & Power Incorporated**

*Quality Products. Service Excellence.*

## Type 4X Stainless Steel Junction Box 1414 N4 PH SS Series

Continuous Hinge Door with Clamps

304 S.S. Part No.	316 S.S. Part No.	Enclosure			Panel	
		H	W	D	H	W
<a href="#">1414N4PHSSC4</a>	<a href="#">1414N4PHS16C4</a>	6.00	4.00	4.00	4.88	2.88
<a href="#">1414N4PHSSE</a>	<a href="#">1414N4PHS16E</a>	6.00	6.00	4.00	4.88	4.88
<a href="#">1414N4PHSSG</a>	<a href="#">1414N4PHS16G</a>	8.00	6.00	3.50	6.75	4.88
<a href="#">1414N4PHSSG4</a>	<a href="#">1414N4PHS16G4</a>	8.00	6.00	4.00	6.75	4.88
<a href="#">1414N4PHSSI</a>	<a href="#">1414N4PHS16I</a>	10.00	8.00	4.00	8.75	6.88
<a href="#">1414N4PHSSK</a>	<a href="#">1414N4PHS16K</a>	12.00	10.00	5.00	10.75	8.88
<a href="#">1414N4PHSSK6</a>	<a href="#">1414N4PHS16K6</a>	12.00	10.00	6.00	10.75	8.88
<a href="#">1414N4PHSSL6</a>	<a href="#">1414N4PHS16L6</a>	12.00	12.00	6.00	10.75	10.88
<a href="#">1414N4PHSSM6</a>	<a href="#">1414N4PHS16M6</a>	14.00	12.00	6.00	12.75	10.88
<a href="#">1414N4PHSSO6</a>	<a href="#">1414N4PHS16O6</a>	16.00	14.00	6.00	14.75	12.88
<a href="#">1414N4PHSSM8</a>	<a href="#">1414N4PHS16M8</a>	14.00	12.00	8.00	12.75	10.88
<a href="#">1414N4PHSSO10</a>	<a href="#">1414N4PHS16O10</a>	16.00	14.00	10.00	14.75	12.88